



LAND CLEARING ATTACHMENTS

DESIGNED FOR DURABILITY

BUILT TO PERFORM

PRODUCT CATALOG



(855) 646-7560

info@brushfox.com

www.brushfox.com





LAND CLEARING ATTACHMENTS

WHY BRUSHFOX_____

A BrushFox brush cutter is an excellent choice for those seeking a high-quality, efficient, and versatile tool for tackling overgrown vegetation and tough brush. Here are some compelling reasons why you should consider buying a BrushFox brush cutter:

1. **Powerful Performance:** BrushFox brush cutters are typically equipped with powerful engines or motors that provide the necessary torque and cutting force to handle even the most stubborn vegetation. This ensures efficient and effective cutting, reducing the time and effort required for clearing tasks.
2. **Versatility:** These brush cutters are designed to handle a wide range of cutting tasks, from clearing thick brush and undergrowth to trimming grass and weeds. This versatility makes them suitable for various outdoor projects, whether you're maintaining your lawn, clearing a field, or managing a large property.
3. **Durable Construction:** BrushFox brush cutters are often built with durability in mind. They feature robust materials and construction techniques that can withstand the rigors of demanding cutting applications, ensuring a long lifespan and reliable performance over time.
4. **Ease of Use:** Many BrushFox models are designed with user-friendly features, such as ergonomic handles, adjustable cutting heights, and intuitive controls. These design elements contribute to a more comfortable and convenient cutting experience, reducing operator fatigue during extended use.
5. **Safety Features:** Brush cutters from reputable brands like BrushFox prioritize safety. Look for models with features like blade guards, anti-vibration systems, and safety switches that help prevent accidents and injuries during operation.
6. **Customizable Attachments:** Depending on the model, BrushFox brush cutters often offer a range of compatible attachments and accessories. This allows you to adapt the tool for different tasks.
7. **Professional Results:** Whether you're a homeowner with a large yard or a professional landscaper, a BrushFox brush cutter can help you achieve clean, well-maintained outdoor spaces. The precision and efficiency of these tools contribute to achieving professional-level results.
8. **Warranty and Customer Support:** BrushFox often provides warranties and dedicated customer support, giving you peace of mind in case you encounter any issues with your brush cutter. A strong warranty demonstrates the manufacturer's confidence in the product's quality and durability.

In conclusion, a BrushFox brush cutter is a compelling choice for those seeking a powerful, versatile, and durable tool to handle various cutting and clearing tasks. Before purchasing, be sure to assess your specific needs, compare different models and features to ensure that a BrushFox brush cutter aligns with your requirements.



LAND CLEARING ATTACHMENTS

MAXHD BRUSH CUTTER—MULCHER

Direct Drive Piston - 4 Blades Plus Carbides

Extreme Open Front design allows Blades to engage toughest vegetation efficiently.

Direct Drive Piston Motor with reversible valve block positioning

1/4" REINFORCED Steel Decking

Hydraulic Motor with Pressure Relief

Four (4) Heat Treated Offset blades

(24) Carbide Tipped Mulching Teeth

Comes Standard with Motor Cover, Hoses, and Couplers



High Torque

30-45 GPM

Direct Drive Motor

High Strength

4 BLADE

Design

Up to

10.0"

Material

<u>MODEL</u>	<u>OAW</u>	<u>Cut</u>	<u>GPM</u>	<u>Weight (lbs)</u>	<u>Brush Size</u>
MAXHD72HF	76"	72"	30-45	1575	10"
MAXHD78HF	82"	78"	30-45	1645	10"



LAND CLEARING ATTACHMENTS

XHD BRUSH CUTTERS

Rugged Cutter with Push Bar—3 Blade

Heavy Duty Push bar integrated with an open front design

Direct Drive Piston Motor with reversible valve block positioning

1/4" REINFORCED Steel Decking

Hydraulic Motor with Pressure Relief

Three (3) Heat treated offset blades

Comes Standard with Motor Cover, Hoses, and Couplers



High Torque

26-40 GPM

Direct Drive Motor

High Strength

3 BLADE

Design

Up to

8.0"

Material

<u>MODEL</u>	<u>OAW</u>	<u>Cut</u>	<u>GPM</u>	<u>Weight (lbs)</u>	<u>Brush Size</u>
XHD72HF	76"	72 "	26-40	1350	8"
XHD78HF	82"	78 "	26-40	1400	8"



LAND CLEARING ATTACHMENTS

HDO SERIES BRUSH CUTTER

Durable and Powerful – 2 Blade Power

Heavy Duty Push bar integrated with an open front design.

Dependable Gearbox Design that maximizes tip speed while tuning itself to a wide variety of loaders ranging from 8 to 26 GPM.

1/4" REINFORCED Steel Decking

Two (2) Heat treated offset blades
Comes Standard with Motor Cover, Hoses, and Couplers



Gearbox Design Maximizing

8-26 GPM

High Torque

High Strength

2 BLADE

Design

Up to

5.0"

Material

<u>MODEL</u>	<u>OAW</u>	<u>Cut</u>	<u>GPM</u>	<u>Weight (lbs)</u>	<u>Brush Size</u>
HDO42LF	48"	42 "	8-15	550	2"
HDO54LF	58"	54 "	15-20	780	3"
HDO66LF	70"	66"	15-20	1175	3"
HDO72LF	76"	72 "	15-20	1250	5"
HDO72STD	76"	72 "	20-26	1250	5"
HDO78STD	82"	78 "	20-26	1300	5"



LAND CLEARING ATTACHMENTS

HD SERIES BRUSH CUTTERS

Dependability and Simplicity- 2 Blade Power

Front design allow blades to engage vegetation aggressively.

Dependable Gearbox Design that maximizes tip speed while tuning itself to a wide variety of loaders ranging from 8 to 26 GPM.

Gearbox and motor cover

1/4" REINFORCED Steel Decking

Comes Standard with Motor Cover, Hoses, and Couplers



Gearbox Design Maximizing

8-26 GPM

High Torque

High Strength

2 BLADE

Design

Up to

4.0"

Material

<u>MODEL</u>	<u>OAW</u>	<u>Cut</u>	<u>GPM</u>	<u>Weight (lbs)</u>	<u>Brush Size</u>
HD42LF	48"	42"	8-15	515	2"
HD66LF	70"	66"	15-20	1100	3"
HD72LF	76"	72"	15-20	1200	3"
HD72STD	76"	72"	20-26	1200	4"
HD78STD	78"	78"	20-26	1300	4"



LAND CLEARING ATTACHMENTS

HD-PTO SERIES BRUSH CUTTERS

Dependability and Simplicity- 2 Blade Power

Cut, clear and mulch unwanted brush, grass and saplings

Heavy-duty design made for rugged applications

Tail wheel is easily adjustable

Heavy-duty gear box and slip clutch

Stump Jumper designed to prevent damage to unit

Operates both forward and backwards

Open deck design allows easier cutting of larger trees



Maximum Durability

7 Gauge

Steel

High Strength

2 BLADE

Design

Up to

4.0"

Material

<u>MODEL</u>	<u>HP Range</u>	<u>Cut Width</u>	<u>Hitch</u>	<u>Weight (lbs)</u>	<u>Brush Size</u>
HD60 3PT	25-55 HP	60"	Cat I	1040	3"
HD72 3PT	40-90 HP	72"	Cat I&II	1240	4"



LAND CLEARING ATTACHMENTS

CXA SERIES

EXCAVATOR BRUSH CUTTERS

Rugged and Powerful Blade Power

- Blades 10" long & 1/2" thick
- Includes 1/4" safety chains
- Deck Thickness 3/16"
- Heavy Duty Deck
- Clockwise Rotation
- Motor protection is handled by a hydraulic pressure relief valve
- Includes standard hoses at 90" long, with 1/2" couplers.



CXA3600X
CXA4200X
2-Blade



CXA4800X
3-Blade
Includes Removable
Safety Cover

Gearbox Design Maximizing

12-25 GPM

Flow

High Strength

2 or 3 BLADE

Design

Up to

5.0

Material

<u>MODEL</u>	<u>Cut</u>	<u>GPM</u>	<u>Max PSI</u>	<u>Blades</u>	<u>Weight (lbs)</u>
CXA3600X	36"	12-20	3000	2	620
CXA4200X	42"	12-20	3000	2	685
CXA4800X	48"	20-25	3000	3	830



LAND CLEARING ATTACHMENTS

XTREME SERIES **EXCAVATOR BRUSH CUTTER MULCHER**

Direct Drive Piston – 3 Blade Plus Carbides

(18) Carbide Tipped Mulching Teeth

Serrated Shark Tooth Cutters

Safety Chains–Removable

Heavy Duty Deck

Clockwise Rotation

Motor protection is handled by a hydraulic pressure relief valve

Comes Standard with Motor Cover, Hoses, and Couplers

Removable Chain Guard–Left Side



High Torque

26-45 GPM

Direct Drive Motor

High Strength

3 BLADE

Design

Up to

10.0"

Material

<u>MODEL</u>	<u>Cut</u>	<u>GPM</u>	<u>Max PSI</u>	<u>Weight (lbs)</u>
4800XTREME	48"	26-38	5000	1200
5400XTREME	54"	33-45	5000	1350



LAND CLEARING ATTACHMENTS

SC SERIES SOIL CONDITIONERS

SKID STEER ATTACHMENTS

Driveline slip clutch protection

Tungsten - carbide teeth

Large solid rubber wheels

Adjustable storage Stand

Teeth are welded in a spiral



Skid Steer



Heavy Duty

Carbide Teeth

Tungsten

High Strength

10" Rotor

Direct Drive Motor

Up to

4.0"

Tilling Depth

<u>MODEL</u>	<u>OAW</u>	<u>Rotor Width</u>	<u>Teeth (Carbide)</u>	<u>Weight (lbs)</u>
SC72	79.5"	72"	88	1100
SC84	91.5"	84 "	104	1200
SC96	103.5"	96"	120	1300



LAND CLEARING ATTACHMENTS

SC SERIES SOIL CONDITIONERS

PTO ATTACHMENTS

Driveline slip clutch protection

Tungsten - carbide teeth

Large solid rubber wheels

Adjustable storage Stand

Teeth are welded in a spiral



Heavy Duty

Carbide Teeth

Tungsten

High Strength

10" Rotor

Direct Drive Motor

Up to

4.0"

Tilling Depth

<u>MODEL</u>	<u>OAW</u>	<u>Rotor Width</u>	<u>Teeth (Carbide)</u>	<u>Weight (lbs)</u>
SC72PTO	82.9"	72"	88	1275
SC84PTO	94.5"	84"	104	1350
SC96PTO	106.5"	96"	120	1505



LAND CLEARING ATTACHMENTS

STUMP SERIES

3-POINT STUMP GRINDERS

PTO TRACTOR ATTACHMENTS

Rugged gear box supports

803 ft/lb. or torque

Heavy-duty base provides stable positioning

Designed for 25-90 HP tractors

65° swing arc



Heavy Duty

Carbide Teeth

Tungsten

Cutting Depth

12"-14"

Below Ground

Cutting Height

25"

Above Ground

<u>MODEL</u>	<u>Hitch Class</u>	<u>Rotor Size</u>	<u>Teeth (Carbide)</u>	<u>Weight (lbs)</u>
SS24PTO	Cat I, II	24"	58	700
SS34PTO	Cat II	34"	92	1000



LAND CLEARING ATTACHMENTS

STUMP SERIES

SKID STEER STUMP GRINDERS

SKID STEER ATTACHMENTS



High Flow



Standard Flow

Wheel Diameter

26"

Large Material

Cutting Teeth

20

Below Ground Depth

11"

MODEL

Dimensions

Max GPM)

Weight (lbs)

High Flow

45-1/2"x37"x40"

20-30 GPM

625

Standard Flow

45-1/2"x37"x40"

15-20 GPM

615



LAND CLEARING ATTACHMENTS

STUMP SERIES

TREE & POST PULLER

SKID STEER ATTACHMENTS

- Weight: 350 lb
- 48"x 28"x 21"
- 24" Jaw Length
- 12" Jaw Opening
- 1/2" High Strength Steel On Jaws
- 1" Tube Frame





LAND CLEARING ATTACHMENTS

GRAPPLE SERIES

EXTREME HD – BRUSH GRAPPLE

SKID STEER ATTACHMENTS

Extra Heavy Duty

Skid Steer Quick Attach

Made with high strength 50,000 psi Steel!

Hydraulic Cylinders Automatically Adjust to Uneven Bucket Loads When Closing

4" Tine Spacing

Gusseted tines for added strength and rock lip to keep material from rolling out



Maximum Grapple Opening

32"

Large Material

Heavy Duty

50,000 psi

Steel

Independent

2"x8"

Hydraulic Cylinders

<u>MODEL</u>	<u>Width (In)</u>	<u>Height</u>	<u>Depth</u>	<u>Weight (lbs)</u>
EXTHD72	72"	30"	38"	875
EXTHD84	84"	30"	38"	975

The bucket tines are 3/8" thick with the outer tines on each end of the bucket being 1/2" thick and all tines stand approximately 4" tall. The top and bottom square tubes that make up the rear frame are 3"x3" and the forward tube behind the tine spreader is 2.5" diameter. The grapple tines are 1/2" thick and connected with a 3/8" web



LAND CLEARING ATTACHMENTS

GRAPPLE SERIES

HD – GRAPPLE BUCKET

SKID STEER ATTACHMENTS

Extra Heavy Duty

Skid Steer Quick Attach

Made with high strength 50,000 psi Steel!

Hydraulic Cylinders Automatically Adjust to Uneven Bucket Loads When Closing

3/8" sides, 1/4" bucket skin, 3/4"x 6" Bevel Edge welded in

Designed for the toughest environments

Includes Cylinder Guards (not shown)



Maximum Grapple Opening

32"

Large Material

Heavy Duty

50,000 psi

Steel

Independent

2"x8"

Hydraulic Cylinders

<u>MODEL</u>	<u>Width (In)</u>	<u>Height</u>	<u>Depth</u>	<u>Weight (lbs)</u>
HDGRAP72	72"	33"	30"	780
HDGRAP84	84"	33"	30"	915

The 84" Flat Bottom Grapple is an excellent "bucket" style grapple that keeps what you're scooping from falling through like a tine style grapple allows. The Flat Bottom covers a wide range of needs. Construction includes: 3/8" sides, 1/4" bucket skin, 3/4"x 6" Bevel Edge welded in



LAND CLEARING ATTACHMENTS

Specifications - Brush Cutters

Model	HD - 42LF	HD-66 LF	HD - 72 LF	HD - 72 STD	HD- 78 STD	HDO-72 STD	HDO-72 LF	HDO-78 STD	XHD-72 HF	XHD-78 HF
Mounting Plate	Universal Quick Attach		Universal Quick Attach		Universal Quick Attach			Universal Quick Attach		
Max Cutting Capacity	2"	3"	3"	4"	4"	5"	5	5	8"	8"
Cutting Diameter	42"	66"	72"	72"	78"	72"	72"	78"	72"	78"
Width	48"	70"	76"	76"	82"	76"	76"	82"	76"	82"
Weight	515	1100	1200	1200	1300	1250	1250	1300	1350	1400
Height	21"	23"	23"	23"	23"	23"	23"	23"	23"	23"
Overall Length	54	80"	80"	80"	80"	80"	80"	80"	80"	80"
Overall Width	48	70"	76"	76"	82"	76"	76"	82"	76"	82"
Product Blades	1/2"x3"	1/2" x4"	1/2" x4"	1/2" x4"	1/2" x4"	1/2" x4"	1/2" x4"	1/2"x4"	1/2" x4"	1/2" x4"
Blade Carrier Type	Lasercut 1/2"	Lasercut 1/2"	Lasercut 1/2"	Lasercut 1/2"	Lasercut 1/2"	Lasercut 1/2"	Lasercut 1/2"	Lasercut 1/2"	Lasercut 3/4"	Lasercut 3/4"
Blade Rotation	CCW	CCW	CCW	CCW	CCW	CCW	CCW	CCW	CCW	CCW
Number of Blades	2	2	2	2	2	2	2	2	3	3
Grinding Teeth	No	No	No	No	No	No	No	No	No	No
Deck Thickness	10 Gauge	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Deck Material	Grade 50	Grade 50	Grade 50	Grade 50	Grade 50	Grade 50	Grade 50	Grade 50	Grade 50	Grade 50
Skid Shoe Thickness/Material	3/8	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Drive Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Drive Type	Gearbox	Gearbox	Gearbox	Gearbox	Gearbox	Gearbox	Gearbox	Gearbox	Direct Drive	Direct Drive
Motor/Gearbox Coupler	Chain Coupling	Chain Coupling	Chain Coupling	Chain Coupling	Chain Coupling	Chain Coupling	Coupling	Coupling	N/A	N/A
Operating PSI Cont	3000	3000	3000	3000	3000	3000	3000	3000	4000	4000
GPM Flow	8-15 GPM	15-20 GPM	15-20 GPM	20-26 GPM	20-26 GPM	20-26 GPM	15-20 GPM	20-26 GPM	26-40 GPM	26-40 GPM
Open or Closed Front	Closed	Closed	Closed	Closed	Closed	Open	Open	Open	Open	Open
Chains Y/N	Yes	Yes	Yes	Yes	Yes	No	No	No	No	No

Model	MAX- HD 72 HF	MAX-HD 78HF	CXA 3600X	CXA 4200X	CXA 4800X	4800 Xtreme	5400 Xtreme
Mounting Plate	Universal Quick Attach		Excavator				
Max Cutting Capacity	10	10"	2	2	5	8	10
Cutting Diameter	72"	78"	36"	42"	48"	48"	54"
Width	76"	82"	42"	48"	54"	63"	63"
Weight	1575	1645	620	685	830	1,200	1,350
Height	27"	27"	24"	24"	24"	26"	27.5"
Overall Length	80"	80"	54"	60	66"	66"	70"
Overall Width	76"	82"	42"	48"	54"	63"	63"
Product Blades	5/8"x6"	5/8"x6"	1/2" X 4" AR400	1/2" X 4" AR400	1/2" X 4" AR400	1/2" X 4" AR400	1/2" X 4" AR400
Blade Carrier Type	Lasercut 3/4"	Lasercut 3/4"	Swing	Swing	Swing	Swing	Swing
Blade Rotation	CW	CW	CW	CW	CW	CCW	CCW
Number of Blades	4	4	2	2	3	3	3
Grinding Teeth	Yes	Yes	No	No	No	18 Carbides	18 Carbides
Deck Thickness	1/4"	1/4"	3/16"	3/16"	3/16"	1/4"	1/4"
Deck Material	Grade 50	Grade 50	Steel	Steel	Steel	Steel	Steel
Skid Shoe Thickness/Material	3/8"	3/8"	3/16"	3/16"	3/16"	1/2"	1/2"
Drive Protection	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Drive Type	Direct Drive	Direct Drive	Gearbox	Gearbox	Gearbox	Direct Drive	Direct Drive
Motor/Gearbox Coupler	N/A	N/A	Chain Coupling	Chain Coupling	Chain Coupling	Over Hung Load Adaptor	
Operating PSI Cont	4000	4000	3000	3000	3000	5000	5000
GPM Flow	30-45 GPM	30-45 GPM	12-20 GPM	12-20 GPM	20-25 GPM	26-38 GPM	33-45 GPM
Open or Closed Front	Open	Open	N/A	N/A	N/A	N/A	N/A
Chains Y/N	No	No	Yes	Yes	Yes/Removeable	Yes/Removeable	Yes/Removeable

Specifications are subject to change



LAND CLEARING ATTACHMENTS

Specifications - PTO

Model	SS24PTO	SS34PTO
Recommended HP	25-60 HP	45-90 HP
Hydraulic GPM	5-20 GPM	5-20 GPM
Rotor Size	24"	34"
Number of Teeth	58	92
Tooth Construction	Carbide steel bolt-in	Carbide steel bolt-in
Cutting Wheel Speed	810 RPM	810 RPM
Cutting Height	25" above ground	25" above ground
Cutting Depth	12" below ground	14" below ground
Maximum Cutting Depth (per pass)	6"	8"
Maximum Horizontal Cut	22"	33"
Swing Arc	65°	65°
Hub Torque	803 ft-lb	803 ft-lb
Over Torque Protection	Slip clutch	Slip clutch
Hitch Category	Cat. I or II	Cat. II
Remotes Required (hydraulic)	1 or 2	1 or 2
Requires 12 Volt DC	No	No
Input Speed	540	540
Weight/Width/Length	700 lb./41"/66.5"	1,000 lb./49"/78"

Options

External Control

Replacement Teeth (each)

Model	HD60 3PT	HD72 3PT
Overall Height	36"	36"
Overall Length	89"	101"
Deck Length	72"	84"
Overall Width	65"	77"
Cutting Width	60"	72"
Deck Thickness	1/4"	1/4"
Shipping Weight	1,040 lb.	1,240 lb.
Hitch Category	Cat. I	Cat. I & II
Input RPM	540	540 RPM
HP Range	25-50 HP	40-90 HP

Specifications are subject to change



LAND CLEARING ATTACHMENTS

Notes:



LAND CLEARING ATTACHMENTS

DESIGNED FOR DURABILITY

BUILT TO PERFORM



(855) 646-7560

info@brushfox.com

www.brushfox.com

Products and Specifications are subject to change. Photos are stock photos, products you receive may have variations depending on the options chosen